



Under-Mount Apron-Front Kitchen Sink K-5826

Features

- Fits minimum 33-inch base cabinet width.
- Single bowl.
- 9" (229 mm) depth provides generous workspace.
- Shortened apron allows sink to be used in most standard cabinetry or retrofitted to existing standard cabinetry.
- Self-Trimming apron overlaps the cabinet face for easy installation and beautiful results.
- Basin slopes 2 degrees toward drain to minimize water pooling.
- Offset drain increases workspace in the sink and storage space underneath.
- Includes cutout templates.

Material

KOHLER® enameled cast iron.

Installation

- No faucet holes.
- Undermount farmhouse.

Recommended Products/Accessories

K-8801 Sink Strainer K-8799 Sink Strainer K-23726 Drain treatment K-23725 Cast iron cleaner

Optional Products/Accessories

K-6449 Steel rack for Whitehaven® K-5826/5827 sinks K-11352 Disposal Flange with Stopper K-9000 P-Trap

Included Components

Additional Components:

Cabinet face cutout template

Countertop cutout template



Codes/Standards

ASME A112.19.1/CSA B45.2

KOHLER® Enameled Cast Iron Kitchen Sink Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	FF	Sea Salt™
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	K4	Cashmere
	FT	Basalt
	58	Thunder™ Grey
	FP	Caviar
	7	Black Black™
	GRL	Grey Lavender
1.10	DGB	Indigo Blue
	PLM	Black Plum







KOHLER®

Under-Mount Apron-Front Kitchen Sink
K-5826







Technical Information

All product dimensions are nominal.

Bowl configuration: Single

Installation: Under-mount Min. base cabinet 33" (838 mm)

width:

Drain hole:

Bowl area: Length: 27-3/4" (705 mm)

Width: 18-1/16" (459 mm) Bowl depth: 9-5/8" (244 mm) Water depth: 9" (229 mm)

3-5/8" (92 mm)

Template: 1214395-7, required, included

1214396-7, required, included

Notes

Install this product according to the installation instructions.

NOTICE: Countertop manufacturer or cutter must use the current product template available at www.kohler.com, or by calling 1-800-4KOHLER. Kohler Co. is not responsible for cutout errors when the incorrect cutout template is used. IMPORTANT! The distance from the top edge of the cabinet to the top of the cabinet door must be at least 6-7/8" (175 mm) to install this sink.

